

## FLOODED DEEP CYCLE BATTERY

## 8 LC GC-HC



Series	LC	Warranty	1 Year
Volts	8	BCI	GC2
Cells	4	Plates/Cell	13
Terminal Type	UTL		
Included Hardware	S/S Hex Cap Screw, Nut, Lock & Flat Washer		
Size & Thread	5/16"-18 x 1-1/2"		

### Charge

Charge Voltage Range	2.45-2.5 V/cell @ 25°C (77°F)		
Float Voltage Range	2.25 V/cell @ 25°C (77°F)		
Self-Discharge Rate	5%-10% per month at 25°C (77°F)		

### Capacity

Cold Crank Amps (CCA) 0°F / -17°C	469		
Marine Crank Amps (MCA) 32°F / 0°C	586		
Reserve Capacity (RC @ 25A)	356 Minutes		
Reserve Capacity (RC @ 75A)	93 Minutes		

Hour Rate	Capacity / AMP Hour	Current / AMPs
@ 5 Hour Rate	140 Ah	28.0 A
@ 10 Hour Rate	156 Ah	15.6 A
@ 20 Hour Rate	177 Ah	8.85 A

Amphère hour capacity ratings based on specific gravity of 1.280. Reduce capacities 5% for specific gravity of 1.265 and 10% for 1.250.

### Specifications




Weight	29.5 kg	65 lbs
Length	259 mm	10.19"
Width	181 mm	7.13"
Height Inc. Term.	279 mm	11"

Product measurements & weights are calculated based on sample data. Individual specifications are subject to vary due to the manufacturing process, battery components & electrolyte levels.

Electrolyte Reserve	57 mm	2.25"
Container	Polypropylene	
Cover	Polypropylene	
Handles	Top Molded Strap Brackets	

### Cycle Life vs. Depth of Discharge



### Voltage vs. Depth of Discharge

